

JCW-CS03

Standard & Flexible Wire Cutting and Stripping Machine



Features

- Best selling standard wire cutting and stripping machine
- High performance and high flexibility for single wire up to 6mm²
- Customizable for processing flat multicore cable and 2 cores twin parallel cable

Technical Data

Function	Single wire, Multicore cable, Zip-cord, Wire measuring, Cut into length, Full stripping, Partial stripping, Mid-stripping, Flat cable slitting, Wire lack sensor, Length correction, Thermal transfer printer		
Raw material	PVC, Teflon, Silicone, Low halogen, Fiberglass, etc	Cutting length (L)	0.1 - 999999 mm
Conductor cross-sections	0.03 - 6 mm ²	Middle strip	13 sections
Stripping length	Front (right) side: 50 mm Rear (left) side: 30 mm		
Production rate	4700 - 9500 pcs/h by 50mm wire length [single/double wire guider]		
Display	4.3" color touchscreen, English / Chinese [other languages on request]		
Compatible peripherals	Cable splitter, wire pre feeder, robot arm, conveyor belt		
Power supply	AC 110V - 220V ± 10%, 50 / 60 Hz	Air supply	0.4 - 0.7 MPa (clean and dry air)
Dimensions	L 460 x W 470 x H 350 mm	Weight	35KG