

Features

· Versatile cut & strip model, capable in cutting and stripping single wire up to 10mm O.d, flat multicore cable, round multicore cable, zip-cord twin flat cable, etc. High speed, low investment

	Techr	nical	Data			
	wire, Multicore cable, Wire measuring, Cut leng Wire run-out sensor, Length correction	th, Ful	l stripping, Partial	stripping,	Mid-stripping, Cut	
Conductor cross-s	sections 0.1 - 16 mm², 10 mm diameter	/	Cutting length (L)	0.1 - 999999 mm	
Stripping length	Front (right) side: 150 mm [partial stripping Rear (left) side: 70 mm [partial stripping]	g]				
Production rate	Single Wire: 2500 pcs/h by 100mm wire lengt Multi-layer stripping: 1600 pcs/h by 100 wire		h			
Twin flat cable	Slit and strip, by changing straightener, guid	e, and	blade (optional)			
Flat multicore cal	ole Outer jacket and inner conductor stripping	ng				
Round multicore	cable Outer jacket stripping	1	Power supply	AC 110V -	220 V ± 10%, 50 / <mark>60 H</mark> z	z
Air supply 0.4 -	0.7 MPa (clean and dry air)	/	Dimensions	L 560 x W	470 x H 370 mm. 45KG	