

JCW-2TM

Multicore Cable Stripping and Crimping Machine

Features

- Round cable: strip and crimp inner cores
- Flat cable: strip outer jacket & inner cores, crimp terminal
- PVC, Teflon, Silicone, Low halogen, Fiberglass cables

Technical Data

| | |
|---------------------------------|--|
| Conductor Cross-sections | 0.05 - 1.5 mm ² [AWG 30 - 16] |
| Crimp force | 2 tons |
| Stroke | 30 mm |
| FFC | On request |
| Rated power | 750 W |
| Power supply | AC 110V- 220 V ± 10%, 50 / 60 Hz |
| Air supply | 0.5 - 0.8 MPa (clean and dry air) |
| Dimensions | L 640 x W 500 x H 1400 mm |
| Weight | 110KG |



JCW-2TN

Multiconductor Sheathed Cable Strip and Crimp Machine

Features

- Side-feed terminal, 2 tons crimp force, high-precision crimping applicator
- Wire range 0.2 - 1.5 mm², servo-motorized wire transfer and stripper
- PVC, Teflon, Silicone, Low halogen, Fiberglass cables

Technical Data

| | |
|---------------------------------|---------------------------------------|
| Conductor Cross-sections | 0.2 - 1.5 mm ² |
| Crimp force | 2 tons |
| Stroke | 30 mm |
| Sheath stripping length | 30 - 60 mm |
| Inner cores numbers | 2 - 15 cores [depends on wire size] |
| Product rate | 700 - 1000 pcs/hr |
| Rated power | 1200 W |
| Power supply | AC 110V- 220 V ± 10%, 50 / 60 Hz |
| Air supply | 0.5 - 0.8 MPa (clean and dry air) |
| Dimensions | L 750 x W 640 x H 1400 mm. 255 KG |

