

JCW-S500 Series

NEW ! Semiautomatic Coaxial Wire Stripping Machine



Features

- High-precision rotary stripping
- Max 10 stripping steps, easily settable via HMI
- Full stripping, partial stripping, multistep stripping
- No mechanical adjustments are required when changing wire sizes

Technical Data

Function	Coaxial cable, single wire, multicore cable, multistep stripping, rotary stripping, full stripping, partial stripping.		
Cable diameter	S500A: 0.5 - 7.5 mm	/ S500B: 1.5 - 15 mm	/ S500C: 3.5 - 23 mm
Stripping length	S500A: 0.1 - 53 mm	/ S500B: 0.1 - 85 mm	/ S500C: 0.1 - 200 mm
Cutting depth increment	0.01 mm		
Blades	S500A: 2 pcs	/ S500B: 4 pcs	/ S500C: 4 pcs
Stripping steps	10		
Production rate	S500A: 700 - 1200 pcs/h	/ S500B: 600 - 700 pcs/h	/ S500C: 600 - 700 pcs/h
Data library	99 programs		
OEM	Yes		
PC Interface	RS232, Foot pedal		
Display	4.3" color touchscreen, English / Chinese [other languages on request]		
Power supply	AC 110V - 220 V \pm 10%, 50 / 60 Hz		
Dimensions	500A: L 540 x W 230 x H 330 mm / 500B: L 640 x W 260 x H 375 mm / 500C: L 960 x W 285 x H 380 mm		
Weight	30 / 34 / 51 KG		